

Laying Specification

®

The coupling and the weight of each Execution of the foundation for honeycomb Grid enable easy and swift laying paving of PE HD types GRASS PAVER (one person lays 50 m in an hour)

Specification of BAIJNATH™ Grass paver

- Drainage bed with 10 15 cm of gravel, crushed stone, etc.
- 2/3 cm of rolled sand to obtain perfect levelling.
- Laying of the paving with grid of PE type GRASS TRAY having the following characteristics :
- UV rays-stable PEHD material.
- Resistance to pressure equal to 200 tons per m²
- Permeable surface equal to 95%
- Carriage-able paving lay as soon as executed without obstructing the growth of the grassy surface.
- Complete filling of the paving with loam soil.
- Water the entire surface so as to obtain a natural compression of the ground.
- Sowing



Load test done by Mumbai Fire Brigade with the load of 16 Ton fire tender at K. Raheja site in Mumbai.

Load test done by K. Raheja with heavy truck, load of 37 Ton at their Mumbai site

BAIJNATH™

Plastic Product Pvt. Ltd.

An ISO TS 16949:2002 Certified Company

R-913 TTC Industrial Area, Rabale, Navi Mumbai, Thane 400 701 India,

Tel. No. 022 65166874 / 75 • Mobile : 9821023003

Email : bajinathplastics@yahoo.com • Website : www.bajinathplastics.com

Sole Selling Agent :

M/s.Olympia Seating Pvt Ltd.,

R 535, TTC Industrial Area, Rabale, Thane-400701.

Tel: 27641601 • Fax : 2764 2580 • Mobile : 9619111970 / 9867435206

Email : olympiaseating@gmail.com